

# Mobile Weighing Cart

ZF/ZFP series

- Small and compact electronics specially developed for mobile weighing.
- Highest level of water and humidity resistance.
- Smaller housing is more robust and withstands impacts and vibration better.
- One electronic board without connectors means reliability for many years in the hardest applications.
- Lower weight of the scale it self; 122(kg), means easier handling of the scale.
- More reliability for the hardest applications and environments.
- Lower power consumption makes scale more user friendly. New batteries are only needed one time per year when weighing 10 pallets per day.
- 4 Penlight batteries can be changed without any effort.
- Auto shut off prevents the batteries to be discharged when client forgets to turn the indicator off.
- Summation of weights with sequence number allows verification if the total load has been weighed.

Equipped with high quality RAVAS/Holland display



ZF20S

# Mobile Weighing Cart

ZF/ZFP series

**Specification**

- Capacity 2000(kg)
- Accuracy 0.1% of the weight applied to the scale
- Graduation 1(kg)
- High contrast display with segment height of 18 (mm).
- Su(m)ation and sequence number giving the number of weights totalised.
- Auto tare giving the net weight added to or taken from the scale.
- Touch panel with push buttons with metal dome, tactile feel gives optimal users interface.
- Totally sealed design to the norm IP 65 (NEMA 4), easy to wash down.
- Operating temperature is -10° to +40°C

- Printer type :Thermal
- Functions :Manual paper feed
- Warning indications by LED :Low battery :No paper :Temperature too low
- Paper :Thermal roll :diameter 40 (mm)
- Print speed :13 lines per second
- Operating temperature :0° to 50°C



without printer



with printer



Model	Capacity (kg)	Printer	Min/Max Fork Height (mm)	Fork Size (mm)			Net Weight (kg)
				Length	Total Width	Fork Width	
ZF20S	2000	without	85 / 205	1150	555	180	117
ZF20L	2000	without	85 / 205	1150	690	180	120
ZFP20S	2000	with	85 / 205	1150	555	180	118
ZFP20L	2000	with	85 / 205	1150	690	180	121

3" (75mm) lowered fork height available.