

Manual Power Lifter (Standard Type)

This time-proven standard model has been redesigned for improved **safety** and **environmental friendliness**.

- Quick-lifting device (except PL-H350-15).
- All models include caster covers as standard accessories.
- Powerful foot-operated parking brake.
- Built-in automatic load check valve device for improved safety.
- Large, transparent guard panel for improved safety.
Manufactured using environmentally friendly polyethylene terephthalate (PET).
- Clean resin sprocket cover.
- Environmentally friendly lead-free paint.
- Compact, lightweight power lifter is capable of smaller turning radius.



Quick-lifting device

Stepping on the quick-lifting magic pedal triples the lifting speed, increasing the work efficiency of power lifter (with no load).



Caster cover



Sprocket cover



Lifting height:1500 mm

PL-H350-15



Lifting height:1500 mm Stainless steel type

PL-H350-15SU



Lifting height:1500 mm

PL-H500-15
PL-H650-15



Lifting height:1500 mm

PL-H 800-15
PL-H1000-15



Lifting height:1500 mm

PL-H 800-15L
PL-H1000-15L



Manual Power Lifter (Standard Type)

Specifications Model	Capacity (kg)	Min. H (mm)	Max. H (mm)	Fork (mm)			Outrigger width (mm)		Overall length (mm)	Overall width (mm)	Overall height (mm)	Steering wheel Dia.φ×width (mm)	Load wheel Dia.φ×width (mm)	Power source	Number of lifting times	Net weight (kg)							
				Length	Load center width	Slide outer width	Outer width	Inner width															
PL-H350-15	350	80	1,500	650	350	165~	508	392	1,175	605	1,900	Rubber 150×45 Urethane 150×38	Urethane 80×38	Manual hydraulic pump	33	92							
PL-H350-15SU						530			1,170	595					107								
PL-H500-15	500	(95)		800	400	270~	550	350	1,230	655	1,950	Stereo 150×45 Urethane 200×42	Urethane 80×73		50〈18〉	138							
PL-H650-15	650					575			1,395						70	157							
PL-H800-15	800	80 (97)		1,000	500	270~	700	500	1,505	855	1,950												
PL-H800-15L									1,705									117 〈42〉	245				
PL-H1000-15	1,000			800	400				1,505											238			
PL-H1000-15L					1,000				500									1,705	245				

※ Minimum lifting height are shown in ()
on the condition that the forks are put on the legs.

※ Lifting times in < > are quick-lifting times
on the condition that no loads are imposed.

Dimensions (PL-H Series)

