

All-Stainless Type Semi-Stainless Type Cold Room Type

A lineup of tough and clean models withstanding rust and low temperatures.

- Taking an active part in food-, chemical-, and electronic-related applications.
- Models with cold room specifications are available at a temperature as low as -10°C.
- A temperature range from -11°C to -35°C is optionally available.



All-Stainless Type

CPFS-15S-107-A



Semi-Stainless Type

CPFG-15S-107-A



Cold Room Type

CPF-15S-107-A



Specifications for All-Stainless Types

● Made of stainless steel in every detail.

Specification Model	Capacity (kg)	Min. H (mm) H ₁	Max. H (mm) H ₂	Fork (mm)					Overall length (mm) L ₄	Overall height (mm) H ₃	Steering wheel Dia. φ width (mm)	Load wheel Dia. φ width (mm)	Net weight (kg)
				Outer width		Length							
				W ₁	L ₁	L ₂	L ₃	W ₂					
CPFS-15M - 85 -A	1,500	80	200	470	850	730	570	170	1,230	1,170	Urethane 175×60	Urethane 80×75	54
CPFS-15S - 107 -A				520	1,070	950	790	220	1,450				64
CPFS-15 L - 107 -A				685	1,220	1,100	940	385	1,600				70
CPFS-15 L - 122 -A				73									
CPFS-15S - 107H-A	1,500	65	185	520	1,070	940	790	220	1,450	1,170	Urethane 175×60	Urethane 65×73	64
CPFS-15J - 107H-A				620	1,220	1,090	940	385	1,600				65
CPFS-15 L - 122H-A				685									73

Specifications for Semi-Stainless Types

● The frame, handle, and shaft of each model are all made of SUS, and the other parts are nickel-chrome plated.

CPFG-15M- 85 -A	1,500	80	200	470	850	730	570	170	1,230	1,170	Urethane 175×60	Urethane 80×75	54
CPFG-15S- 107 -A				520	1,070	950	790	220	1,450				64
CPFG-15 L- 107 -A				685	1,220	1,100	940	385	1,600				70
CPFG-15 L- 122 -A				73									
CPFG-15S -107H-A	1,500	65	185	520	1,070	940	790	220	1,450	1,170	Urethane 175×60	Urethane 65×73	64
CPFG-15J -107H-A				620	1,220	1,090	940	385	1,600				65
CPFG-15 L -122H-A				685									73
CPFG-30 L- 122 -A				3,000	85	205	685	1,220	1,160				920

*Due to limitations inherent in the tank plating process, some surfaces may be subject to brush electroplating.


Specifications for Cold Room Types

● Paint finish. The main pump parts and sliding parts are made of SUS.


CPF-15M - 85-A	1,500	80	200	470	850	730	570	170	1,230	1,170	Nylon 175×60	Nylon 80×75	56
CPF-15S - 107-A				520	1,070	950	790	220	1,450				66
CPF-15 L - 107-A				685	1,220	1,100	940	385	1,600				72
CPF-15 L - 122-A				75									
CPF-15S -107H-A	1,500	65	185	520	1,070	940	790	220	1,450	1,170	Nylon 175×60	Nylon 65×75	66
CPF-15 L -122H-A				685	1,220	1,090	940	385	1,600				75
CPF-20S - 107-A				520									1,070
CPF-20 L - 122-A				2,000	80	200	685	1,220	1,100				940

◎ is available on request.

Dimensions



Option



Parking Brake
Mountable to all models.