


# Manual Power Lifter (Economy Type)

This economy model offers basic functionality. All models are upgraded with a quick-lifting device. Includes a well-regarded pump pedal as a standard accessory.

- Built-in automatic load check valve device for improved safety.
- Transparent guard panel ensures wide field of vision.
- Compact, lightweight power lifter is capable of smaller turning radius.
- Sprocket cover.



Featuring two to three times the lifting speed

## (Patented) Quick-lifting device (Built-in)

Increases the lifting speed of the fork two to three times for light loads, improving the working efficiency of the power lifter. A safety feature automatically switches the lifting speed to normal when the load exceeds a certain limit.



## (Option) Pump handle

Mountable on all manual economy models.



Lifting height: 1200 mm

PL-H200-12S



Lifting height: 1200 mm

PL-H350-12S



Lifting height: 1500 mm

PL-H350-15S



Lifting height: 1500 mm

PL-H500-15S



Lifting height: 1500 mm

PL-H650-15S




## Manual Power Lifter (Economy Type)

Specifications	Capacity (kg)	Min. H (mm)	Max. H (mm)	Fork (mm)			Outrigger width (mm)		Overall length (mm)	Overall width (mm)	Overall height (mm)	Steering wheel Dia. φ × width (mm)	Load wheel Dia. φ × width (mm)	Power source	Number of lifting times	Net weight (kg)
				Length	Load center	Slide outer width	Outer width	Inner width								
Model		A1	A	B	C	D	E1	E2	F	G	H					
PL-H200- 8S	200	75	850	550	300	135~470	470	356	935	530	1,200	Rubber 125X38	Urethane 75X32	Hydraulic foot pedal	16 ( 8 )	47
PL-H200-12S		(90)	1,200												24 (12)	53
PL-H350-12S	350	80	1,500	650	350	165~530	510	396	1,170	575	1,600	Rubber 150X40	Urethane 80X38	Hydraulic foot pedal	55 (18)	84
PL-H350-15S			1,500												46 (23)	89
PL-H500-12S	500	(95)	1,200	650	350	215~575	550	400	1,180	625	1,600	Urethane 80X38	Urethane 80X38	Hydraulic foot pedal	55 (18)	96
PL-H500-15S			1,200												69 (23)	103
PL-H650-15S	650		1,500	800	400	265~575		350	1,335		1,925	Urethane 80X73	Urethane 80X73	Hydraulic foot pedal	104 (36)	125

※ Minimum lifting height is shown in ( ) on the condition that the forks are put on the legs.  
 ※ Economy types (PL-H350 to PL-H650) cannot be modified.

※ Lifting times in ( ) are quick-lifting times on the condition that no loads are imposed.

## Dimensions (PL-H-S Series)



Steering wheel Load wheel